

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.839 g/cm ³
Viscosity @ 100°C (cSt)	8.8 cSt
Viscosity @ 40°C (cSt)	44 cSt
Viscosity Index	185
Viscosity CCS @ -35°C (cP)	5100 cP
T.B.N (mg KOH/g)	9.1 mg KOH/g
Sulphated Ash Mass (%)	0.7 %
Zinc (%)	0.09 %
Colour	Amber
Phosphorus (%)	0.07 %
Flash Point (°C)	>200 °C
Calcium (%)	0.11 %

ECO-V 0W-20

Fully Synthetic

Official Approvals:

Volvo VCC RBS0-2AE

Recommended by Comma for applications requiring any of the following:

ACEA C5, API SN

Product Features:

- Fully synthetic engine oil specifically developed for latest technology Volvo engines from 2013 onwards.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 13.09.2024