



S-OIL SEVEN ATF MULTI

FULLY SYNTHETIC MULTI PURPOSE AUTOMATIC TRANSMISSION FLUID

Product Description

S-OIL SEVEN ATF MULTI is a premium ATF based on highly refined API Group III base oil and suitable for use in wide range of Asian, European and American vehicles. Its excellent thermal and oxidation stability prevents deposit or corrosive matters in your gearbox, so it provides stable operation of your ATF and long oil life.

Applications

- Wide range of 4/5/6/8 speed automatic gearboxes in Asian, European and American passenger vehicles
- Follow the vehicle's ATF fluid change interval and performance level recommended in your owner's manual

Features and Potential Benefits

- Full synthetic base oil helps maintain oils initial conditions thanks to good stability and high viscosity index
- Exceptional friction and anti-shudder performances with advanced technology
- Excellent viscosity stability in operation
- Good thermal stability, resistance to oxidation and wear protection

Performance Level

- Recommended for use where the following specifications are called for :
Allison(C4/295/389), BMW(400 272/400 275/407 858/407 859/024 249/024 359/026 922/402 413/403 248/403 249/542 290/407 765/407 807), Chrysler/Dodge/Jeep(+/-+2/+3/+4/AS68RC/SP-III), Mercedes/Daimler(MB 236.5/6/7/8/9/91/10/11), Ford/Lincoln/Mercury(2-QDX/2-QSM/5-QM/5-DM/8-QAW/9-QMMS/WSS-M2C9EE-A1), GM(II/IIID/IIIE/IIIG/IIIH/T-IV/Type A Suffix A), Honda(Z-1), Hyundai/Kia(Red-1K/T-4/SP-II/SP-III), Isuzu(II/III), Jaguar(JLM 20238/20292/21044), JASO(M315 1A), MAN 339(A), Mazda(F1/JWS33317/9-QMM5/M-III/Type T-IV), Mitsubishi(J2/SP-II/SP-III), Nissan(402/Matic-D/J/K), Porsche(204 41/205 09/205 28/547 00), PSA(169756), Renault(D2), Saab(T-IV), SSANGYONG(DSIH 5M-66), Subaru(HP), Suzuki (3314/7), Toyota(D-II/T/T-III/T-IV), VW(052 055/052 162/052 990/055 025/000 162), Volvo(1161521/1161540/1161640), ZF(TE-ML 11A/B)

Typical Properties

Test Items	Method	Unit	Properties	
Specific Gravity	ASTM D1298	-	0.848	
Color	ASTM D1500	-	Red	
Viscosity	40°C	ASTM D445	cSt	36.8
	100°C	ASTM D445	cSt	7.0
Viscosity Index	ASTM D2270	-	153	
Flash Point	ASTM D92	°C	232	
Pour Point	ASTM D97	°C	-46	

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN ATF MULTI
2020.08.26.



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet is obtainable via your commercial adviser.